



**WR-E1/M1
(Black / Silver)**



**WR-E2/M2
(Black / Silver)**



25 98 45
▶▶▶ Various of RFID readers

RFID READER

Site Security, Access Control, Elevator Control



Specification

Function	Model	Model
	 WR-E1/M1	 WR-E2/M2
RFID card type	EM and Compatible type Mifare	EM and Compatible type Mifare
Active distance	EM : 7~12cm/Mifare : 3~5cm	EM : 7~12cm/Mifare : 3~5cm
Verification time	100ms	100ms
Power consumption	Avg.300mA	Avg.300mA
Communication	WG 34	WG 34
LED	3	3
Transmit distance	100M	100M
ESD protection	-+2.5KV	-+2.5KV
Power requirement	9~24VDC(200mA)	9~24VDC(200mA)
Operation Temperature	0 °C ~ 65°C	0 °C ~ 65°C
Operation humidity	5% ~ 95%	5% ~ 95%
Built-in Watch Dog	●	●
Card Collision Algorithm	●	●
Weatherproof	●	●
Self-diagnostic	●	●
Tamper Switch	N/A	N/A
Surge Protection	●	●
Buzzer	●	●
Dimension (mm)	100 x 35 x 25	100 x 45 x 25
Weight (g.)	82	100

Welcome to **CHIYU**